

FortiGate 3700F Series

FG-3700F and FG-3701F



Highlights

Gartner Magic Quadrant Leader for both Network Firewalls and SD-WAN.

Security-Driven Networking FortiOS delivers converged networking and security.

Unparalleled Performance with Fortinet's patented / SPU / vSPU processors.

Enterprise Security with consolidated Al / ML-powered FortiGuard Services.

Hyperscale Security to secure any edge at any scale.

High Performance with Flexibility

The FortiGate 3700F Series enables organizations to build security-driven networks that can weave security deep into their datacenter and across their hybrid IT architecture to protect any edge at any scale.

Powered by a rich set of AI/ML-based FortiGuard Services and an integrated security fabric platform, the FortiGate 3700F Series delivers coordinated, automated, end-to-end threat protection across all use cases.

The industry's first integrated Zero Trust Network Access (ZTNA) enforcement within an NGFW solution, FortiGate 3700F automatically controls, verifies, and facilitates user access to applications delivering consistent convergence with a seamless user experience.

IPS	NGFW	Threat Protection	Interfaces
86 Gbps	80 Gbps	75 Gbps	Multiple 400 GE QSFP-DD, 200GE QSFP56, 100 GE QSFP28, 50 GE SFP56, 40 GE QSFP+, 25 GE SFP28, 10 GE SFP+ slots, and 10 GE / GE RJ45 port



Available in



Appliance



Virtual





Cloud



Container

FortiOS Everywhere

FortiOS, Fortinet's Advanced Operating System

FortiOS enables the convergence of high performing networking and security across the Fortinet Security Fabric. Because it can be deployed anywhere, it delivers consistent and context-aware security posture across network, endpoint, and multi-cloud environments.

FortiOS powers all FortiGate deployments whether a physical or virtual device, as a container, or as a cloud service. This universal deployment model enables the consolidation of many technologies and use cases into a simplified, single policy and management framework. Its organically built best-of-breed capabilities, unified operating system, and ultra-scalability allows organizations to protect all edges, simplify operations, and run their business without compromising performance or protection.

FortiOS dramatically expands the Fortinet Security Fabric's ability to deliver advanced Al/ ML-powered services, inline advanced sandbox detection, integrated ZTNA enforcement, and more, provides protection across hybrid deployment models for hardware, software, and Software-as-a-Service with SASE.

FortiOS expands visibility and control, ensures the consistent deployment and enforcement of security policies, and enables centralized management across large-scale networks with the following key attributes:

- Interactive drill-down and topology viewers that display real-time status
- On-click remediation that provides accurate and quick protection against threats and abuses
- Unique threat score system correlates weighted threats with users to prioritize investigations



Intuitive easy to use view into the network and endpoint vulnerabilities



Visibility with FOS Application Signatures

FortiConverter Service

FortiConverter Service provides hassle-free migration to help organizations transition from a wide range of legacy firewalls to FortiGate Next-Generation Firewalls quickly and easily. The service eliminates errors and redundancy by employing best practices with advanced methodologies and automated processes. Organizations can accelerate their network protection with the latest FortiOS technology.



FortiGuard Services

Network and File Security

Services provide protection against network-based and file-based threats. This consists of Intrusion Prevention (IPS) which uses AI/M models to perform deep packet/SSL inspection to detect and stop malicious content, and apply virtual patching when a new vulnerability is discovered. It also includes Anti-Malware for defense against known and unknown file-based threats. Anti-malware services span both antivirus and file sandboxing to provide multilayered protection and are enhanced in real-time with threat intelligence from FortiGuard Labs. Application Control enhances security compliance and offers real-time application visibility.

Web / DNS Security

Services provide protection against web-based threats including DNS-based threats, malicious URLs (including even in emails), and botnet/command and control communications. DNS filtering provides full visibility into DNS traffic while blocking high-risk domains, and protects against DNS tunneling, DNS infiltration, C2 server ID and Domain Generation Algorithms (DGA). URL filtering leverages a database of 300M+ URLs to identify and block links to malicious sites and payloads. IP Reputation and anti-botnet services prevent botnet communications, and block DDoS attacks from known sources.

SaaS and Data Security

Services address numerous security use cases across application usage as well as overall data security. This consists of Data Leak Prevention (DLP) which ensures data visibility, management and protection (including blocking exfiltration) across networks, clouds, and users, while simplifying compliance and privacy implementations. Separately, our Inline Cloud Access Security Broker (CASB) service protects data in motion, at rest, and in the cloud. The service enforces major compliance standards and manages account, user and cloud application usage. Services also include capabilities designed to continually assess your infrastructure, validate that configurations are working effectively and secure, and generate awareness of risks and vulnerabilities that could impact business operations. This includes coverage across IoT devices for both IoT detection and IoT vulnerability correlation.

Zero-Day Threat Prevention

Zero-day threat prevention entails Fortinet's AI-based inline malware prevention, our most advanced sandbox service, to analyze and block unknown files in real-time, offering subsecond protection against zero-day and sophisticated threats across all NGFWs. The service also has a built-in MITRE ATT&CK® matrix to accelerate investigations. The service focuses on comprehensive defense by blocking unknown threats while streamlining incident response efforts and reducing security overhead.

OT Security

The service provides OT detection, OT vulnerability correlation, virtual patching, OT signatures, and industry-specific protocol decoders for overall robust defense of OT environments and devices.



Secure Any Edge at Any Scale

Powered by Security Processing Unit (SPU)

Traditional firewalls cannot protect against today's content- and connection-based threats because they rely on off-the-shelf hardware and general-purpose CPUs, causing a dangerous performance gap. Fortinet's custom SPU processors deliver the power you need—up to 520Gbps—to detect emerging threats and block malicious content while ensuring your network security solution does not become a performance bottleneck.

ASIC Advantage



Network Processor 7 NP7

Network Processors operate inline to deliver unmatched performance and scalability for critical network functions. Fortinet's breakthrough SPU NP7 network processor works in line with FortiOS functions to deliver:

- Hyperscale firewall, accelerated session setup, and ultra-low latency
- Industry-leading performance for VPN, VXLAN termination, hardware logging, and elephant flows



Content Processor 9 CP9

Content Processors act as co-processors to offload resource-intensive processing of security functions. The ninth generation of the Fortinet Content Processor, the CP9, accelerates resource-intensive SSL (including TLS 1.3) decryption and security functions while delivering:

- Pattern matching acceleration and fast inspection of real-time traffic for application identification
- IPS pre-scan/pre-match, signature correlation offload, and accelerated antivirus processing



FortiCare Services

Fortinet is dedicated to helping our customers succeed, and every year FortiCare Services help thousands of organizations get the most from our Fortinet Security Fabric solution. Our lifecycle portfolio offers Design, Deploy, Operate, Optimize, and Evolve services. Operate services offer device-level FortiCare Elite service with enhanced SLAs to meet our customer's operational and availability needs. In addition, our customized account-level services provide rapid incident resolution and offer proactive care to maximize the security and performance of Fortinet deployments.



Use Cases

Next Generation Firewall (NGFW)

- FortiGuard Labs' suite of Al-powered Security Services—natively integrated with your NGFW—secures web, content, and devices and protects networks from ransomware and sophisticated cyberattacks
- Real-time SSL inspection (including TLS 1.3) provides full visibility into users, devices, and applications across the attack surface
- Fortinet's patented SPU (Security Processing Unit) technology provides industry-leading high-performance protection



Segmentation

- Dynamic segmentation adapts to any network topology to deliver true end-to-end security—from the branch to the datacenter and across multi-cloud environments
- Ultra-scalable, low latency, VXLAN segmentation bridges physical and virtual domains with Layer 4 firewall rules
- Prevents lateral movement across the network with advanced, coordinated protection from FortiGuard Security Services detects and prevents known, zero-day, and unknown attacks



Secure SD-WAN

- FortiGate WAN Edge powered by one OS and unified security and management framework and systems transforms and secures WANs
- Delivers superior quality of experience and effective security posture for work-from-any where models, SD-Branch, and cloud-first WAN use cases
- Achieve operational efficiencies at any scale through automation, deep analytics, and self-healing



Mobile Security for 4G, 5G, and IoT

- SPU-accelerated, high performance CGNAT and IPv6 migration options, including: NAT44, NAT444, NAT64/ DNS64, NAT46 for 4G Gi/sGi, and 5G N6 connectivity and security
- RAN Access Security with highly scalable and highest-performing IPsec aggregation and control Security Gateway (SecGW)
- User plane security enabled by full threat protection and visibility into GTP-U inspection

Datacenter Deployment (NGFW, IPS, Segmentation)



Hardware

FortiGate 3700F Series



Hardware Features



Interfaces

- 1. 1 x USB and 1 x Console Port
- 2. 2 × 10 GE / GE RJ45 Management Ports
- 3. 2 × 50 GE SFP56 / 25 GE SFP28 / 10 GE SFP+ HA1/HA2 Ports
- 4. 4 × 25 GE SFP28 / 10 GE SFP+ / GE SFP ULL Ports
- 5. 18 × 50 GE SFP56 / 25 GE SFP28 / 10 GE SFP+ / 1 GE SFP Ports
- 6. 4×400 GE QSFP-DD / 200 GE QSFP56 / 100 GE QSFP28 / 40 GE QSFP+ Ports

Trusted Platform Module (TPM)

The FortiGate 3700F Series features a dedicated module that hardens physical networking appliances by generating, storing, and authenticating cryptographic keys. Hardware-based security mechanisms protect against malicious software and phishing attacks.

Specifications

	FG-3700F	FG-3701F			
Interfaces and Modules					
Hardware Accelerated 400GE QSFP-DD/ 200GE QSFP56/ 100GE QSFP28/ 40GE QSFP+ Ports	4				
Hardware Accelerated 50 GE SFP56/ 25 GE SFP28/ 10 GE SFP+ Ports	18				
Hardware Accelerated 25 GE SFP28/ 10 GE SFP+/ GE SFP ULL Ports	4				
Hardware Accelerated 50 GE SFP56/ 25 GE SFP28/ 10 GE SFP+ HA1/HA2 Ports	2				
10GE/ GE RJ45 Management Ports	2				
USB Ports (Client / Server)	1 / 1				
Console Port	1				
Onboard Storage	-	2× 2TB			
Trusted Platform Module (TPM)	Yes				
Included Transceivers	2x SFP+ (SR 10 GE)				
System Performance — Enterprise Traffic Mix					
IPS Throughput ²	86 Gbj	os			
NGFW Throughput ^{2, 4}	80 Gbp	os			
Threat Protection Throughput ^{2,5}	75 Gbps				
System Performance and Capacity					
IPv4 Firewall Throughput (1518 / 512 / 64 byte, UDP)	589 / 589 / 420 Gbps				
IPv6 Firewall Throughput (1518 / 512 / 86 byte, UDP)	589 / 589 / 420 Gbps				
Firewall Latency (64 byte, UDP)	3.56 µs / 1.45 µs*				
Firewall Throughput (Packet per Second)	630 Mpps				
Concurrent Sessions (TCP)	140 Million				
New Sessions/Second (TCP)	930 000				
Firewall Policies	200 00				
IPsec VPN Throughput (512 byte) ¹	160 Gb				
Gateway-to-Gateway IPsec VPN Tunnels	40 000				
Client-to-Gateway IPsec VPN Tunnels	200 000				
SSL-VPN Throughput ⁶	16 Gbps				
Concurrent SSL-VPN Users (Recommended Maximum, Tunnel Mode)	30 000				
SSL Inspection Throughput (IPS, avg. HTTPS) ³	55 Gbps				
SSL Inspection CPS (IPS, avg. HTTPS) ³	57 000				
SSL Inspection Concurrent Session (IPS, avg. HTTPS) ³	15 Million				
Application Control Throughput (HTTP 64K) ²	190 Gbps				
CAPWAP Throughput (HTTP 64K)	65 Gbps				
Virtual Domains (Default / Maximum)	10 / 500				
Maximum Number of FortiSwitches Supported	300				
Maximum Number of FortiAPs (Total / Tunnel)	4096 / 2048				
Maximum Number of FortiTokens	20 00	0			
High Availability Configurations	Active-Active, Active-P	assive, Clustering			

Note: All performance values are "up to" and vary depending on system configuration. ¹ IPsec VPN performance test uses AES256-SHA256.

 $^{\rm 2}$ IPS (Enterprise Mix), Application Control, NGFW and Threat Protection are measured with Logging enabled.

 $^{\scriptscriptstyle 3}$ SSL Inspection performance values use an average of HTTPS sessions of different cipher suites.

Height x Width x Length (inches) 3.5 × 17.44 × 23.9 Height x Width x Length (mm) 88.9 × 443 × 607.1 Weight 47.1 lbs (21.4 kg) 48.7 lbs (22.1 kg) Form Factor (supports EIA/non-EIA standards) Rack Mount, 2 RU AC Power Supply 100–240 VAC, 60/50 Hz Power Consumption (Average / Maximum) 590 W / 1140 W 600 W / 1150 W AC Current (Maximum) 12A@100V, 9A@240V Heat Dissipation 3887 BTU/h 3921 BTU/h Redundant Power Supplies (Hot Swappable) Yes (Default dual AC PSU for 1+1 Redundancy) Power Supply Efficiency Rating 80Plus Compliant Operating Temperature 32°–104°F (0°–40°C) Storage Temperature -31°–158°F (-35°–70°C) Humidity 5% to 90% non-condensing Noise Level 70.4 dBA Forced Airflow Front to Back Operating Altitude Up to 10 000 ft (3048 m) Compliance FCC Part 15 Class A, RCM, VCCI, CE, UL/CUL, CB					
Height x Width x Length (inches)3.5 × 17.44 × 23.9Height x Width x Length (mm)88.9 × 443 × 607.1Weight47.1 lbs (21.4 kg)48.7 lbs (22.1 kg)Form Factor (supports EIA/non-EIA standards)Rack Mount, 2 RUAC Power Supply100-240 VAC, 60/50 HzPower Consumption (Average / Maximum)590 W / 1140 W600 W / 1150 WAC Current (Maximum)12A@100V, 9A@240VHeta Dissipation3887 BTU/h3921 BTU/hRedundant Power Supplies (Hot Swappable)Yes (Default dual AC PSU for 1+1 Redundancy)Power Supply Efficiency Rating80Plus CompliantOperating Temperature32°-104°F (0°-40°C)Storage Temperature-31°-158°F (-35°-70°C)Humidity5% to 90% non-condensingNoise Level70.4 dBAForced AirflowFront to BackOperating AltitudeUp to 10 000 ft (3048 m)ComplianceFCC Part 15 Class A, RCM, VCCI, CE, UL/CUL, CB		FG-3700F	FG-3701F		
Height x Width x Length (mm) 88.9 × 443 × 607.1 Height x Width x Length (mm) 88.9 × 443 × 607.1 Weight 47.1 lbs (21.4 kg) 48.7 lbs (22.1 kg) Form Factor (supports EIA/non-EIA standards) Rack Mount, 2 RU AC Power Supply 100–240 VAC, 60/50 Hz Power Consumption (Average / Maximum) 590 W / 1140 W 600 W / 1150 W AC Current (Maximum) 12A@100V, 9A@240V Heat Dissipation 3887 BTU/h 3921 BTU/h Redundant Power Supplies (Hot Swappable) Yes (Default dual AC PSU for 1+1 Redundancy) Power Supply Efficiency Rating 80Plus Compliant Operating Environment and Certifications 20°–104°F (0°–40°C) Storage Temperature -31°–158°F (-35°–70°C) Humidity 5% to 90% non-condensing Noise Level 70.4 dBA Forced Airflow Front to Back Operating Altitude Up to 10 000 ft (3048 m) Compliance FCC Part 15 Class A, RCM, VCCI, CE, UL/CUL, CB	Dimensions and Power				
Weight 47.1 bs (21.4 kg) 48.7 bs (22.1 kg) Form Factor (supports EIA/non-EIA standards) Rack Mount, 2 RU AC Power Supply 100–240 VAC, 60/50 Hz Power Consumption (Average / Maximum) 590 W / 1140 W 600 W / 1150 W AC Current (Maximum) 12A@100V, 9A@240V Heat Dissipation 3887 BTU/h 3921 BTU/h Redundant Power Supplies (Hot Swappable) Yes (Default dual AC PSU for 1+1 Redundancy) Power Supply Efficiency Rating 80Plus Compliant Operating Temperature 32°–104°F (0°–40°C) Storage Temperature -31°–158°F (-35°–70°C) Humidity 5% to 90% non-condensing Noise Level 70.4 dBA Forced Airflow Front to Back Operating Altitude Up to 10 000 ft (3048 m) Compliance FCC Part 15 Class A, RCM, VCCI, CE, UL/CUL, CB	Height x Width x Length (inches)	3.5 × 17.4	14 × 23.9		
Form Factor (supports EIA/non-EIA standards) Rack Mount, 2 RU AC Power Supply 100–240 VAC, 60/50 Hz Power Consumption (Average / Maximum) 590 W / 1140 W 600 W / 1150 W AC Current (Maximum) 12A@100V, 9A@240V Heat Dissipation 3887 BTU/h 3921 BTU/h Acedundant Power Supplies (Hot Swappable) Yes (Default dual AC PSU for 1+1 Redundancy) Power Supply Efficiency Rating 80Plus Compliant Operating Environment and Certifications Operating Temperature 32°–104°F (0°–40°C) Storage Temperature -31°–158°F (-35°–70°C) Humidity 5% to 90% non-condensing Noise Level 70.4 dBA Forced Airflow Front to Back Operating Altitude Up to 10 000 ft (3048 m) Compliance FCC Part 15 Class A, RCM, VCCI, CE, UL/CUL, CB	Height x Width x Length (mm)	88.9 × 443 × 607.1			
AC Power Supply 100–240 VAC, 60/50 Hz Power Consumption (Average / Maximum) 590 W / 1140 W 600 W / 1150 W AC Current (Maximum) 12A@100V, 9A@240V Heat Dissipation 3887 BTU/h 3921 BTU/h Redundant Power Supplies (Hot Swappable) Yes (Default dual AC PSU for 1+1 Redundancy) Power Supply Efficiency Rating 80Plus Compliant Operating Environment and Certifications Operating Temperature 31°–158°F (-35°–70°C) Humidity 5% to 90% non-condensing Noise Level 70.4 dBA Forced Airflow Front to Back Operating Altitude Up to 10 000 ft (3048 m) Compliance FCC Part 15 Class A, RCM, VCCI, CE, UL/CUL, CB	Weight	47.1 lbs (21.4 kg)	48.7 lbs (22.1 kg)		
Power Consumption (Average / Maximum) 590 W / 1140 W 600 W / 1150 W AC Current (Maximum) 12A@100V, 9A@240V Heat Dissipation 3887 BTU/h 3921 BTU/h Redundant Power Supplies (Hot Swappable) Yes (Default dual AC PSU for 1+1 Redundancy) Power Supply Efficiency Rating 80Plus Compliant Operating Environment and Certifications Operating Temperature 32°-104°F (0°-40°C) Storage Temperature -31°-158°F (-35°-70°C) Humidity 5% to 90% non-condensing Noise Level 70.4 dBA Forced Airflow Front to Back Operating Altitude Up to 10 000 ft (3048 m) Compliance FCC Part 15 Class A, RCM, VCCI, CE, UL/CUL, CB	Form Factor (supports EIA/non-EIA standards)	Rack Mount, 2 RU			
Average / Maximum) 12A@100V, 9A@240V AC Current (Maximum) 12A@100V, 9A@240V Heat Dissipation 3887 BTU/h 3921 BTU/h Redundant Power Supplies Yes (Default dual AC PSU for 1+1 Redundancy) Yes Power Supply Efficiency Rating 80Plus Compliant Deparating Environment and Certifications Operating Temperature 32°-104°F (0°-40°C) Storage Temperature Storage Temperature -31°-158°F (-35°-70°C) Humidity Noise Level 70.4 dBA Storage Temperature Forced Airflow Front to Back Deparating Altitude Operating Altitude Up to 10 000 ft (3048 m) Compliance	AC Power Supply	100-240 VAC, 60/50 Hz			
Heat Dissipation 3887 BTU/h 3921 BTU/h Redundant Power Supplies (Hot Swappable) Yes (Default dual AC PSU for 1+1 Redundancy) Power Supply Efficiency Rating 80Plus Compliant Operating Environment and Certifications 32°-104°F (0°-40°C) Storage Temperature -31°-158°F (-35°-70°C) Humidity 5% to 90% non-condensing Noise Level 70.4 dBA Forced Airflow Front to Back Operating Altitude Up to 10 000 ft (3048 m) Compliance FCC Part 15 Class A, RCM, VCCI, CE, UL/cUL, CB	Power Consumption (Average / Maximum)	590 W / 1140 W	600 W / 1150 W		
Yes (Default dual AC PSU for 1+1 Redundancy) Power Supply Efficiency Rating 80Plus Compliant Operating Environment and Certifications 9000000000000000000000000000000000000	AC Current (Maximum)	12A@100V, 9A@240V			
Hot Swappable) (Default dual AC PSU for 1+1 Redundancy) Power Supply Efficiency Rating 80Plus Compliant Operating Environment and Certifications 32°-104°F (0°-40°C) Storage Temperature -31°-158°F (-35°-70°C) Humidity 5% to 90% non-condensing Noise Level 70.4 dBA Forced Airflow Front to Back Operating Altitude Up to 10 000 ft (3048 m) Compliance FCC Part 15 Class A, RCM, VCCI, CE, UL/cUL, CB	Heat Dissipation	3887 BTU/h	3921 BTU/h		
Operating Environment and Certifications Operating Temperature 32°-104°F (0°-40°C) Storage Temperature -31°-158°F (-35°-70°C) Humidity 5% to 90% non-condensing Noise Level 70.4 dBA Forced Airflow Front to Back Operating Altitude Up to 10 000 ft (3048 m) Compliance FCC Part 15 Class A, RCM, VCCI, CE, UL/cUL, CB	Redundant Power Supplies (Hot Swappable)	100			
Operating Temperature 32°-104°F (0°-40°C) Storage Temperature -31°-158°F (-35°-70°C) Humidity 5% to 90% non-condensing Noise Level 70.4 dBA Forced Airflow Front to Back Operating Altitude Up to 10 000 ft (3048 m) Compliance FCC Part 15 Class A, RCM, VCCI, CE, UL/CUL, CB	Power Supply Efficiency Rating	80Plus Compliant			
Storage Temperature -31°-158°F (-35°-70°C) Humidity 5% to 90% non-condensing Noise Level 70.4 dBA Forced Airflow Front to Back Operating Altitude Up to 10 000 ft (3048 m) Compliance FCC Part 15 Class A, RCM, VCCI, CE, UL/CUL, CB	Operating Environment and Certifications				
Humidity 5% to 90% non-condensing Noise Level 70.4 dBA Forced Airflow Front to Back Operating Altitude Up to 10 000 ft (3048 m) Compliance FCC Part 15 Class A, RCM, VCCI, CE, UL/CUL, CB	Operating Temperature	32°-104°F (0°-40°C)			
Noise Level 70.4 dBA Forced Airflow Front to Back Operating Altitude Up to 10 000 ft (3048 m) Compliance FCC Part 15 Class A, RCM, VCCI, CE, UL/cUL, CB	Storage Temperature	-31°-158°F (-35°-70°C)			
Forced Airflow Front to Back Operating Altitude Up to 10 000 ft (3048 m) Compliance FCC Part 15 Class A, RCM, VCCI, CE, UL/cUL, CB	Humidity	5% to 90% non-condensing			
Operating Altitude Up to 10 000 ft (3048 m) Compliance FCC Part 15 Class A, RCM, VCCI, CE, UL/CUL, CB	Noise Level	70.4 dBA			
Compliance FCC Part 15 Class A, RCM, VCCI, CE, UL/cUL, CB	Forced Airflow	Front to Back			
CE, UL/cUL, CB	Operating Altitude	Up to 10 000 ft (3048 m)			
Certifications USGv6/IPv6	Compliance				
	Certifications	USGv6/IPv6			

* Latency based on Ultra Low Latency (ULL) ports.

⁴ NGFW performance is measured with Firewall, IPS and Application Control enabled.

⁵ Threat Protection performance is measured with Firewall, IPS, Application Control and Malware Protection enabled.

⁶ Uses RSA-2048 certificate.



Ordering Information

Product	SKU	Description
FortiGate 3700F	FG-3700F	$4\times$ 400 GE QSFP-DD slots, $4x$ ULL SFP28 slots and 20× 50 GE SFP56 slots (including 18x ports, 2x HA ports), 2× 10GE RJ45 Management Ports, SPU NP7 and CP9 hardware accelerated, and 2 AC power supplies.
FortiGate 3701F	FG-3701F	4× 400 GE QSFP-DD slots, 4x ULL SFP28 slots and 20× 50 GE SFP56 slots (including 18x ports, 2x HA ports), 2× 10GE RJ45 Management Ports, SPU NP7 and CP9 hardware accelerated, 4 TB SSD onboard storage, and 2 AC power supplies.
Optional Accessories/Spares	SKU	Description
Rack Mount Sliding Rails	SP-FG3040B-RAIL	Rack mount sliding rails for FG-1000C/-DC, FG-1200D, FG-1500D/DC, FG-3040B/-DC, FG-3140B/- DC, FG-3240C/-DC, FG-3000D/-DC, FG-3100D/-DC, FG-3200D/-DC, FG-3400/3401E, FG- 3600/3601E, FG-3700D/-DC, FG-3700DX, FG-3810D/-DC and FG-3950B/-DC.
AC Power Supply	FG-7040E-PS-AC	1500W AC Power Supply for FG-3700F, FG-3701F, FG-7030E, FG-7040E, FG-6000F, and FG-3900E series (not compatible for use with FG-7060E), does not include SP-FGPCORC15-XX power cord
1 GE SFP LX Transceiver Module	FN-TRAN-LX	1 GE SFP LX transceiver module for all systems with SFP and SFP/SFP+ slots.
1 GE SFP RJ45 Transceiver Module	FN-TRAN-GC	1 GE SFP RJ45 transceiver module for all systems with SFP and SFP/SFP+slots.
1 GE SFP SX Transceiver Module	FN-TRAN-SX	1 GE SFP SX transceiver module for all systems with SFP and SFP/SFP+ slots.
10 GE SFP+ RJ45 Transceiver Module	FN-TRAN-SFP+GC	10 GE SFP+ RJ45 transceiver module for systems with SFP+ slots.
10 GE SFP+ Transceiver Module, Short Range	FN-TRAN-SFP+SR	10 GE SFP+ transceiver module, short range for all systems with SFP+ and SFP/SFP+ slots.
10 GE SFP+ Transceiver Module, Long Range	FN-TRAN-SFP+LR	10 GE SFP+ transceiver module, long range for all systems with SFP+ and SFP/SFP+ slots.
10 GE SFP+ Transceiver Module, Extended Range	FN-TRAN-SFP+ER	10 GE SFP+ transceiver module, extended range for all systems with SFP+ and SFP/SFP+ slots.
10GE SFP+ Transceiver Module, 30km Long Range	FN-TRAN-SFP+BD27	10GE SFP+ transceiver module, 30km long range single BiDi for systems with SFP+ and SFP/SFP+ slots (connects to FN-TRAN-SFP+BD33, ordered separately)
10GE SFP+ Transceiver Module, (connects to FN- TRAN-SFP+BD27, ordered separately)	FN-TRAN-SFP+BD33	10GE SFP+ transceiver module, 30km long range single BiDi for systems with SFP+ and SFP/SFP+ slots (connects to FN-TRAN-SFP+BD27, ordered separately)
10 GE SFP+ Active Direct Attach Cable, 10m / 32.8 ft	SP-CABLE-ADASFP+	10 GE SFP+ active direct attach cable, 10m / 32.8 ft for all systems with SFP+ and SFP/SFP+ slots.
25 GE SFP28 Transceiver Module, Short Range	FN-TRAN-SFP28-SR	25 GE SFP28 transceiver module, short range for all systems with SFP28 slots.
25 GE SFP28 Transceiver Module, Long Range	FG-TRAN-SFP28-LR	25 GE SFP28 transceiver module, long range for all systems with SFP28 slots.
40 GE QSFP+ Transceiver Module, Short Range	FN-TRAN-QSFP+SR	40 GE QSFP+ transceiver module, short range for all systems with QSFP+ slots.
40 GE QSFP+ Transceiver Module, Short Range BiDi	FG-TRAN-QSFP+SR-BIDI	40 GE QSFP+ transceiver module, short range BiDi for all systems with QSFP+ slots.
40 GE QSFP+ Transceiver Module, Long Range	FN-TRAN-QSFP+LR	40 GE QSFP+ transceiver module, long range for all systems with QSFP+ slots.
100 GE QSFP28 Transceivers, Short Range	FN-TRAN-QSFP28-SR	100 GE QSFP28 transceivers, 4 channel parallel fiber, short range for all systems with QSFP28 slots.
100 GE QSFP28 Transceivers, Long Range	FN-TRAN-QSFP28-LR	100 GE QSFP28 transceivers, 4 channel parallel fiber, long range for all systems with QSFP28 slots.
100 GE QSFP28 Transceivers, CWDM4	FN-TRAN-QSFP28-CWDM4	100 GE QSFP28 transceivers, LC connectors, 2KM for all systems with QSFP28 slots.
100 GE QSFP28 BIDI Transceiver Module	FN-TRAN-QSFP28-BIDI	100 GE QSFP28 BIDI transceiver module, 100m MMF LC connector, for systems with QSFP28 slots.
25 GE SFP28 Passive Direct Attach Cable	FN-CABLE-SFP28-1	25 GE SFP28 passive direct attach cable 1m for systems with SFP28 slots.
25 GE SFP28 Passive Direct Attach Cable	FN-CABLE-SFP28-3	25 GE SFP28 passive direct attach cable 3m for systems with SFP28 slots.
25 GE SFP28 Passive Direct Attach Cable	FN-CABLE-SFP28-5	25 GE SFP28 passive direct attach cable 5m for systems with SFP28 slots.
100 GE QSFP28 Breakout to 4× 25 GE SFP28 Passive Direct Attach Cable	FN-CABLE-QSFP28-4SFP28-1	100 GE QSFP28 breakout to 4×25 GE SFP28 passive direct attach cable, 1m
100 GE QSFP28 Breakout to 4× 25 GE SFP28 Passive Direct Attach Cable	FN-CABLE-QSFP28-4SFP28-3	100 GE QSFP28 breakout to 4×25 GE SFP28 passive direct attach cable, 3m
100 GE QSFP28 Breakout to 4× 25 GE SFP28 Passive Direct Attach Cable	FN-CABLE-QSFP28-4SFP28-5	100 GE QSFP28 breakout to 4× 25 GE SFP28 passive direct attach cable, 5m
400 GE QSFPDD Transceiver Module, 10km Range	FN-TRAN-QSFPDD-LR4	400 GE QSFPDD transceiver module, 10km range, SMF, for systems with QSFP-DD slots
400 GE QSFPDD Transceiver Module, 2km Range	FN-TRAN-QSFPDD-FR4	400 GE QSFPDD transceiver module, 2km range, SMF, for systems with QSFP-DD slots
400 GE QSFPDD Transceiver Module, 4 Channel Parallel Fiber	FN-TRAN-QSFPDD-DR4	400 GE QSFPDD transceiver module, 4 channel parallel fiber, short range, for systems with QSFP-DE slots
400 GE QSFPDD Transceiver Module, 8 Channel Parallel Fiber	FN-TRAN-QSFPDD-SR8	400 GE QSFPDD transceiver module, 8 channel parallel fiber, short range, for systems with QSFP-DE slots
400 GE QSFPDD Passive Direct Attach Cable, 1m	FN-CABLE-QSFPDD-DAC-01	400 GE QSFPDD passive Direct Attach Cable, 1m, for systems with QSFP-DD slots.
400 GE QSFPDD Passive Direct Attach Cable, 2.5m	FN-CABLE-QSFPDD-DAC-B5	400 GE QSFPDD passive Direct Attach Cable, 2.5m, for systems with QSFP-DD slots.

Subscriptions

			Bundles			
Service Category	Service Offering	A-la-carte	Enterprise Protection	Unified Threat Protection	Advanced Threat Protection	
FortiGuard Security Services	IPS Service				•	
	Anti-Malware Protection (AMP) — Antivirus, Mobile Malware, Botnet, CDR, Virus Outbreak Protection and FortiSandbox Cloud Service	•	•	•	•	
	URL, DNS & Video Filtering Service	•	•	•		
	Anti-Spam		•	•		
	Al-based Inline Malware Prevention Service	•	•			
	Data Loss Prevention Service ¹	•	•			
	OT Security Service (OT Detection, OT Vulnerability correlation, Virtual Patching, OT Signature / Protocol Decoders) ¹	٠				
	Application Control		included with FortiCare Subscription			
	CASB SaaS Control		included with FortiCare Subscription			
SD-WAN and SASE Services	SD-WAN Underlay Bandwidth and Quality Monitoring Service	•				
	SD-WAN Overlay-as-a-Service for SaaS-based overlay network provisioning	•				
	SD-WAN Connector for FortiSASE Secure Private Access	•				
	FortiSASE subscription including cloud management and 10Mbps bandwidth license ²	•				
NOC and SOC Services	FortiGuard Attack Surface Security Service (IoT Detection, IoT Vulnerability Correlation, and Security Rating Updates) ¹	•	•			
	FortiConverter Service	•	•			
	Managed FortiGate Service	•				
	FortiGate Cloud (SMB Logging + Cloud Management)	•				
	FortiAnalyzer Cloud	•				
	FortiAnalyzer Cloud with SOCaaS	•				
	FortiGuard SOCaaS	•				
Hardware and Software Support	FortiCare Essentials	•				
	FortiCare Premium	•	•	•	•	
	FortiCare Elite	•				
Base Services	Internet Service (SaaS) DB Updates					
	GeoIP DB Updates		included with For	iCare Subscription		
	Device/OS Detection Signatures	insided with ottoble subscription				
	Trusted Certificate DB Updates					
	DDNS (v4/v6) Service					

1. Full features available when running FortiOS 7.4.1 2. Desktop Models only



FortiGuard Bundles

FortiGuard Labs delivers a number of security intelligence services to augment the FortiGate firewall platform. You can easily optimize the protection capabilities of your FortiGate with one of these FortiGuard Bundles.

FortiCare Elite

FortiCare Elite offers enhanced SLAs and quick issue resolution through a dedicated support team. It provides single-touch ticket handling, extended Extended End-of-Engineering-Support for 18 months, and access to the new FortiCare Elite Portal for a unified view of device and security health.

Fortinet CSR Policy

Fortinet is committed to driving progress and sustainability for all through cybersecurity, with respect for human rights and ethical business practices, making possible a digital world you can always trust. You represent and warrant to Fortinet that you will not use Fortinet's products and services to engage in, or support in any way, violations or abuses of human rights, including those involving illegal censorship, surveillance, detention, or excessive use of force. Users of Fortinet products are required to comply with the Fortinet EULA and report any suspected violations of the EULA via the procedures outlined in the Fortinet Whistleblower Policy.





www.fortinet.com

Copyright © 2023 Fortinet, Inc. All rights reserved. Fortinet*, FortiGate*, Fo